# 7 × 57
# FMJ 140 GRS SB757A



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.

## PROPERTIES

| | | | |
|---|---|---|---|
| **BULLET** | TYPE | | FMJ |
| | WEIGHT | grs | 140 |
| | DIAMETER | in | 0.284 |
| | SECTIONAL DENSITY | lb/in² | 0.248 |
| | MATERIAL OF JACKET | | CuZn 10 |
| **BALLISTIC COEFFICIENT** | | G1 | 0.429 |
| | | G7 | 0.214 |
| **CARTRIDGE** | LENGTH | in | 3.071 |
| **POWER FACTOR ESTIMATED** | | kgr·fps | 366.9 |
| **TEST BARREL LENGTH** | | in | 23½ |
| **SUGGESTED USE** | | | Range, Match/Competition |
| **FEATURES** | | | Reliable Functioning, Non-expanding, No Barrel Leading |

## PACKAGING

| | | |
|---|---|---|
| **BOXES PER CASE** | | 20 |
| **WEIGHT PER CASE** | lb | 23 |

## BALLISTICS

| DISTANCE | y | MUZZLE | 100 | 200 | 300 | 400 |
|---|---|---|---|---|---|---|
| VELOCITY | fps | 2,621 | 2,413 | 2,214 | 2,026 | 1,846 |
| ENERGY | ft·lb | 2,136 | 1,810 | 1,524 | 1,275 | 1,059 |

| DISTANCE | y | 50 | 100 | 200 | 300 | 400 |
|---|---|---|---|---|---|---|
| POINTS OF IMPACT | in | -0.3 | 0.0 | -4.0 | -15.1 | -34.7 |

