40 S&W NONTOX TFMJ

V311232
180 GRS



After firing the cartridge is free from toxic exposure to barium, lead, mercury, antimony. It does not pollute the environment, does not endanger the shooter's health with combustion products, and does not leave harmful residue in the gun. It ensures safe shooting in closed premises and on target ranges. Unique patented primer design.

PROPERTIES

BULLET	TYPE		TFMJ
	WEIGHT	grs	180
		g	11.70
	SECTIONAL DENSITY	lb/in²	0.161
	MATERIAL OF JACKET		CuZn 10
	NUMBER		2317
BALLISTIC COEFFICIENT		G1	0.191
CARTRIDGE	WEIGHT	g	16.7
	LENGTH	mm	28.80
CASINGS			Factory Brass
POWER FACTOR ESTIMATED		kgr·fps	174.2
+P AMMUNITION			No
TEST BARREL LENGTH		mm	102
SUGGESTED USE			Range, Match/Competition
FEATURES			Fully Encapsulated Bullet, Reliable Functioning, Non-expanding, No Barrel Leading

PACKAGING

BOXES PER CASE		20
WEIGHT PER CASE	kg	18.3
	lb	40

BALLISTICS

DISTANCE	m	MUZZLE	25	50	100
VELOCITY	m/s	295	287	280	268
ENERGY	J	509	483	459	419

DISTANCE	m	12,5	25	50	100
POINTS OF IMPACT	cm	0.2	0.0	-5.9	-41.6

