38 SPECIAL NONTOX TFMJ

V311422
158 GRS



After firing the cartridge is free from toxic exposure to barium, lead, mercury, antimony. It does not pollute the environment, does not endanger the shooter's health with combustion products, and does not leave harmful residue in the gun. It ensures safe shooting in closed premises and on target ranges. Unique patented primer design.

PROPERTIES

BULLET	TYPE		TFMJ
	WEIGHT	grs	158
		g	10.25
	SECTIONAL DENSITY	lb/in²	0.177
	MATERIAL OF JACKET		CuZn 30
	NUMBER		N/A
BALLISTIC COEFFICIENT		G1	0.184
CARTRIDGE	WEIGHT	g	15.1
	LENGTH	mm	38.60
CASINGS			Factory Brass
POWER FACTOR ESTIMATED		kgr·fps	137.9
+P AMMUNITION			No
TEST BARREL LENGTH		mm	190
SUGGESTED USE			Range, Match/Competition
FEATURES			Fully Encapsulated Bullet, Reliable Functioning, Non-expanding, No Barrel Leading

PACKAGING

BOXES PER CASE		20
WEIGHT PER CASE	kg	16.4
	lb	36

BALLISTICS

DISTANCE	m	MUZZLE	25	50	100
VELOCITY	m/s	266	260	255	244
ENERGY	J	363	347	332	305

DISTANCE	m	12,5	25	50	100
POINTS OF IMPACT	cm	0.4	0.0	-7.6	-51.5

