

CASINGS

POWER FACTOR ESTIMATED

+P AMMUNITION

SUGGESTED USE

FEATURES

TEST BARREL LENGTH

10 mm AUTO TFMJ V312422 180 GRS

After firing the cartridge is free from toxic exposure to barium, lead, mercury, antimony. It does not pollute the environment, does not endanger the shooter's health with combustion products, and does not leave harmful residue in the gun. It ensures safe shooting in closed premises and on target ranges. Unique patented primer design.

	PROPERTIES			
	BULLET	ТҮРЕ		TFMJ
		WEIGHT	grs	180
			g	11.70
		SECTIONAL DENSITY	lb/in²	0.161
		MATERIAL OF JACKET		CuZn 10
		NUMBER		2317
	BALLISTIC COEFFICIENT		G1	0.191
	CARTRIDGE	WEIGHT	g	17.3
		LENGTH	mm	32.00

kgr-fps

Factory Brass

Match/Competition

Reliable Functioning,

209.7

No

150

Range,

	Non-expanding, No Barrel Leading		
PACKAGING			
BOXES PER CASE	20		
WEIGHT PER CASE	kg 18.6		
	lb 41		

	BALLISTICS									
DISTANCE		MUZZLE								
		355	339	326	305					
		737	673	621	543					
DISTANCE		12,5								
		-0.1	0.0	-3.8	-29.2					

