# 10 mm AUTO XRG-D

V312482
130 GRS



This solid copper hollow-point bullet construction results in near 100% weight retention regardless of the barriers encountered. Light-for-caliber bullet weights produce low perceived recoil, high velocity, and reliable expansion from today's compact personal defense handguns. The impressive, real-world performance of XRG Defense has been proven by many European Law Enforcement units.

## PROPERTIES

| | | | |
|---|---|---|---|
| **BULLET** | TYPE | | XRG-D |
| | WEIGHT | grs | 130 |
| | | g | 8.40 |
| | SECTIONAL DENSITY | lb/in² | N/A |
| | MATERIAL OF JACKET | | - |
| | NUMBER | | 2365 |
| **BALLISTIC COEFFICIENT** | | G1 | 0.130 |
| **CARTRIDGE** | WEIGHT | g | 14 |
| | LENGTH | mm | 32.00 |
| **CASINGS** | | | N/A |
| **POWER FACTOR ESTIMATED** | | kgr-fps | 177.1 |
| **+P AMMUNITION** | | | No |
| **TEST BARREL LENGTH** | | mm | 150 |
| **SUGGESTED USE** | | | N/A |
| **FEATURES** | | | N/A |

## PACKAGING

| | | |
|---|---|---|
| **BOXES PER CASE** | | 40 |
| **WEIGHT PER CASE** | kg | 15.4 |
| | lb | 33.9 |

## BALLISTICS

| DISTANCE | m | MUZZLE | 25 | 50 | 100 |
|---|---|---|---|---|---|
| VELOCITY | m/s | 415 | 382 | 355 | 315 |
| ENERGY | J | 723 | 613 | 528 | 417 |

| DISTANCE | m | 12,5 | 25 | 50 | 100 |
|---|---|---|---|---|---|
| POINTS OF IMPACT | cm | -0.3 | 0.0 | -2.7 | -23.4 |

