

300 AAC BLACKOUT FMJ SUBSONIC

V341302
200 GRS

Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

| BULLET | TYPE | | FMJ SUBSONIC | |
|------------------------|-------------------|--------------------|--|-------|
| | WEIGHT | grs | 200 | |
| | | g | 13.00 | |
| | SECTIONAL DENSITY | lb/in² | 0.301 | |
| | | MATERIAL OF JACKET | | |
| | NUMBER | | | 2950 |
| BALLISTIC COEFFICIENT | | | G1 | 0.558 |
| | | | G7 | 0.242 |
| MRD | | | m | 70 |
| CARTRIDGE | WEIGHT | g | 19.9 | |
| | LENGTH | mm | 56.00 | |
| CASINGS | | | Factory Brass | |
| POWER FACTOR ESTIMATED | | kg-fps | 212.0 | |
| +P AMMUNITION | | | No | |
| TEST BARREL LENGTH | | mm | 406 | |
| SUGGESTED USE | | | Range, Match/Competition | |
| FEATURES | | | Reliable Functioning, Non-expanding, No Barrel Leading | |

PACKAGING

| | | |
|-----------------|----|------|
| BOXES PER CASE | | 50 |
| WEIGHT PER CASE | kg | 20.8 |
| | lb | 46.3 |

BALLISTICS

| | | | | | | |
|----------------------|-----|--------|-------|--------|--------|--------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 323 | 308 | 296 | 285 | 275 |
| ENERGY | J | 678 | 616 | 568 | 528 | 492 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | 9.9 | 0.0 | -98.5 | -309.2 | -640.7 |
| POINTS OF IMPACT MRD | cm | 3.5 | -12.7 | -123.9 | -347.3 | -691.5 |

