# 308 WIN. TXRG

V342292
110 GRS

New generation lead free bullets Modern, highly efficient design incorporating a boat-tail base with a new, pointed tip for a flat trajectory and maximum retained energy. Blue plastic tip enhances expansion at all ranges while the solid copper construction maximizes weight retention.

## PROPERTIES

| | | | |
|---|---|---|---|
| **BULLET** | TYPE | | TXRG |
| | WEIGHT | grs | 110 |
| | | g | 7.10 |
| | SECTIONAL DENSITY | lb/in² | 0.166 |
| | MATERIAL OF JACKET | | - |
| | NUMBER | | 2973 |
| **BALLISTIC COEFFICIENT** | | G1 | 0.288 |
| | | G7 | 0.145 |
| **MRD** | | m | 167 |
| **CARTRIDGE** | WEIGHT | g | 22 |
| | LENGTH | mm | 71.10 |
| **CASINGS** | | | N/A |
| **POWER FACTOR ESTIMATED** | | kgr·fps | 279.7 |
| **+P AMMUNITION** | | | No |
| **TEST BARREL LENGTH** | | mm | 600 |
| **SUGGESTED USE** | | | N/A |
| **FEATURES** | | | N/A |

## PACKAGING

| | | |
|---|---|---|
| **BOXES PER CASE** | | 12 |
| **WEIGHT PER CASE** | kg | 6.5 |
| | lb | 14.3 |

## BALLISTICS

| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
|---|---|---|---|---|---|---|
| VELOCITY | m/s | 843 | 739 | 642 | 553 | 470 |
| ENERGY | J | 2,523 | 1,938 | 1,465 | 1,087 | 785 |

| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
|---|---|---|---|---|---|---|
| POINTS OF IMPACT | cm | -0.5 | 0.0 | -13.1 | -50.2 | -119.6 |
| POINTS OF IMPACT MRD | cm | 1.4 | 3.8 | -5.4 | -38.6 | -104.2 |