

9,3 × 74 R

XRG V342652 250 GRS



S&B's original solid copper hunting bullet designed for deep penetration and high weight retention on the toughest game animals.



PROPERTIES

| | | | |
|-------------------------------|--------------------|--------------------|-------|
| BULLET | TYPE | | XRG |
| | WEIGHT | grs | 250 |
| | | g | 16.20 |
| | SECTIONAL DENSITY | lb/in ² | N/A |
| | MATERIAL OF JACKET | | - |
| | NUMBER | | 2979 |
| BALLISTIC COEFFICIENT | | G1 | 0.348 |
| | | G7 | 0.175 |
| MRD | | m | 151 |
| CARTRIDGE | WEIGHT | g | 32.2 |
| | LENGTH | mm | 96.50 |
| CASINGS | | | N/A |
| POWER FACTOR ESTIMATED | | kgf-fps | 612.0 |
| +P AMMUNITION | | | No |
| TEST BARREL LENGTH | | mm | 650 |
| SUGGESTED USE | | | N/A |
| FEATURES | | | N/A |
| PACKAGING | | | |
| BOXES PER CASE | | | 4 |
| WEIGHT PER CASE | | kg | 3.1 |
| | | lb | 7.3 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|--------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 746 | 665 | 589 | 518 | 451 |
| ENERGY | J | 4,508 | 3,582 | 2,814 | 2,176 | 1,648 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | 0.0 | 0.0 | -17.3 | -63.0 | -145.5 |
| POINTS OF IMPACT MRD | cm | 1.9 | 3.8 | -9.7 | -51.7 | -130.4 |

